

Berge junction box All in one solution

Serial Server - Uninterruptible Power Supply - Breakout Panel - Ethernet Switch –



The BERGE Junction Box provides a serial server solution with 4 independent COM channels RS232 and RS422. It also features a UPS power backup system. In addition the system has a 4x ports Ethernet 10/100 switch. Furthermore it has a Breakout Panel with 4x USB 2.0-3.0, Line In-Line Out and Keypad connector.

The BERGE all in one solution eliminates the need for installing and servicing multiple system units. Installation, servicing and unit replacement is quick and easy.

Serial Server Interface:

RS232/422 4-in-1 serial port interface.

All channels are fully isolated channel to channel and channel to chassis.

Independent Operations Mode for each Serial Port

Support protocols TCP/IP, UDP, DHCP, PPPoE, Dynamic DNS

TCP server operating mode

TCP Client operating mode

UDP operating modes

Peer connection

Modem mode

Ethernet Interface

4 port 10/100 Mbps switch

UPS Interface

Intelligent UPS

2200mAh 14.6V lithium ION battery

SMBUS slave and I2C master

HID USB to SMBUS BRIDGE

Input 9-36Vdc

output 19Vdc

Input/Output current 6A/10A peak

Charge between 9-36V, 3A

OS detects battery state


Typically backup time 30-60 minutes depending on screen size


Certifications:

IEC 60495*

* To be certified

Connectors junction box





Connectors panel pc

